M O D E R N L I N E

BIOFA
WOHNGESUND & NACHHALTIG

NATÜRLICH & KLIMASCHÜTZEND

Catalog

- What would you like to do - BIOFA product recommendations
- Product overview
  - Standard products in ascending order of item numbers
  - Special products in ascending order of item numbers

Edition 2024

HEALTHY LIVING
IN HARMONY WITH NATURE

BIOFA makes it possible!

Healthy living, sustainability, best quality and experience since 1980, that's what BIOFA offers - your team of experts when it comes to oils, varnishes and paints for inside and outside, which are made from natural, high-quality raw materials!

Why natural products are so important!

Because HEALTHY LIVING is not a luxury and
- People spend 80% of their daily lives indoors
- A healthy and active life is not possible without a healthy indoor climate
- Our body becomes stressed by substances in the air that it is not familiar with and we then feel exhausted and tired.

It is a matter of course for BIOFA to inform its customers in detail about the composition of the products through a special full declaration. The "transparent formula" helps consumers select all everyday products in order to identify possible allergenic or sensitizing ingredients.

In addition, the BIOFA top sellers already have an SHI product passport, which lists all the relevant certifications for healthy living, climate protection and state subsidies. The certificates and information can be accessed quickly via the SHI database.

SHI product passports for BIOFA products

BIOFA
WOHNGESUND & NACHHALTIG

Anyone who currently wants to receive funding for a new house from the KfW Reconstruction Loan Institution must meet sustainability criteria. These are confirmed by the **Sustainable Buildings quality seal, or QNG for short**

Products with the QNG Ready seal meet these criteria!

BIOFA Furniture Oil 2049 and Parquet Oil special 2059

BIOFA SOLIMIN Silicate Paint 3051 and SOLIMIN Quartz Brush Plaster 3055

Indoor area

	item no.	product	page
wooden furniture			
external furniture surfaces			
non layer-forming oils	2049	Furniture Oil, solvent-free	8
layer-forming oils	2033	Hard Wax Oil, mat	8
	2044	Universal Hard Oil, semi mat	8
	2055	Hard Wax Oil, semi gloss	8
colored primer	2110	Color Oil, solvent-free	11
wax	2060	Hard Wax, semi gloss	9
varnishes	5201, 52011	Wood Varnish Aqua, colorless and colored	14
enamel paints	5134, 5135	VERNILUX Aqua Enamel Paint, semi mat	14
	5136	VERNILUX Aqua Enamel Paint, semi gloss	14
primer	1211	Primer Aqua	7
interior furniture surfaces	5005	Natural Shellac Enhancer, solvent-free	14
worktops	2052	Worktop Oil, solvent-free	8
floors			
wooden floors			
wooden floors without joints			
nonlayer-forming oils	2059	Parquet Oil Special, solvent-free	9
layer-forming oils	2033	Hard Wax Oil, mat	8
	2044	Universal Hard Oil, semi mat	8
	2055	Hard Wax Oil, semi gloss	8
colored primer	2110	Color Oil, solvent-free	11
soaps	2091	Floor Soap natural	10
	2092	Floor Soap white	10
whitening for hardwoods	2093	Hard Wood Lye	10
whitening for softwoods	2094	Soft Wood Lye	11
wooden floors with joints			
layer-forming oils	2033	Hard Wax Oil, mat	8
	2044	Universal Hard Oil, semi mat	8
	2055	Hard Wax Oil, semi gloss	8
colored primer	2110	Color Oil, solvent-free	11
soaps	2091	Floor Soap natural	10
	2092	Floor Soap white	10
whitening for hardwoods	2093	Hard Wood Lye	10
whitening for softwoods	2094	Soft Wood Lye	11
cork floors			
non layer-forming oils	2059	Parquet Oil Special, solvent-free	9
layer-forming oils	2033	Hard Wax Oil, mat	8
	2044	Universal Hard Oil, semi mat	8
	2055	Hard Wax Oil, semi gloss	8
colored primer	2110	Color Oil, solvent-free	11
mineral floors			
screed	2100, 21001	Stone Oil, colorless and colored	11
primer	3754	Universal Wood Primer	12
unglazed tiles	2100	Stone Oil, colorless	11
primer	3754	Universal Wood Primer	12
linoleum flooring	2033	Hard Wax Oil, mat	8
	2044	Universal Hard Oil, semi mat	8
	2055	Hard Wax Oil, semi gloss	8



Indoor area

interior fittings	item no.	product	page
walls and room doors			
layer-forming oils	2033	Hard Wax Oil, mat	8
	2044	Universal Hard Oil, semi mat	8
	2055	Hard Wax Oil, semi gloss	8
colored primer	2110	Color Oil, solvent-free	11
color Wax	2087, 20871	Color Wax, solvent-free, colorless and colored	10
varnishes	5201, 52011	Wood Varnish Aqua, colorless and colored	14
enamel paints	5134, 5135	VERNILUX Aqua Enamel Paint, semi mat	14
	5136	VERNILUX Aqua Enamel Paint, semi gloss	14
primer	1211	Primer Aqua, solvent-free	7
soaps	2091	Floor Soap natural	10
	2092	Floor Soap white	10
whitening for hardwoods	2093	Hard Wood Lye	10
whitening for softwoods	2094	Soft Wood Lye	11
railings, beams, ...			
layer-forming oils	2033	Hard Wax Oil, mat	8
	2044	Universal Hard Oil, semi mat	8
	2055	Hard Wax Oil, semi gloss	8
colored primer	2110	Color Oil, solvent-free	11
varnishes	5201,52011	Wood Varnish Aqua, colorless and colored	14
enamel paints	5134, 5135	VERNILUX Aqua Enamel Paint, semi mat	14
	5136	VERNILUX Aqua Enamel Paint, semi gloss	14
primer	1211	Primer Aqua, solvent-free	7
windows and exterior doors			
varnishes	5201,52011	Wood Varnish Aqua, colorless and colored	14
enamel paints	5134, 5135	VERNILUX Aqua Enamel Paint, semi mat	14
	5136	VERNILUX Aqua Enamel Paint, semi gloss	14
primer	1211	Primer Aqua, solvent-free	7
heating elements			
enamel paints	5134, 5135	VERNILUX Aqua Enamel Paint, semi mat	14
	5136	VERNILUX Aqua Enamel Paint, semi gloss	14
toys			
non layer-forming oils	2052	Worktop Oil, solvent-free	8
enamel paints	5134, 5135	VERNILUX Aqua Enamel Paint, semi mat	14
	5136	VERNILUX Aqua Enamel Paint, semi gloss	14
primer	1211	Primer Aqua, solvent-free	7
Toy paint	8005 1-17	Toy paint Aqua	15
weld- and saliva-resistant final coating	8045, 8245	Hard Oil Aqua, semi mat / mat	15

BIOFA Naturprodukte W. Hahn GmbH ◆ Dobelstraße 22 ◆ D-73087 Bad Boll ◆ T: +49 7164-9405 0 ◆ F: +49 7164-9405 96 ◆ www.biofa-de.com ◆ info@biofa-de.com

Indoor area

	item no.	product	page
walls and ceilings			
plaster / plasterboard, gypsum and cellulose fibreboard / old paint / wallpaper / condrete			
natural rexin paint	**3011, 3011 1-4**	PRIMASOL Wall Paint, solvent-free, semi mat	11
primer for sanding and highly absorbent substrates	**1440**	Universal Primer, solvent-free	7
primer for levelled and differently absorbent substrates	**3046**	SOLIMIN Special Primer, solvent-free	11
mineral silicate paint	**3051, 3051 1-4**	SOLIMIN Mineral Paint, solvent-free	11
primer for sanding and higly absorbent substrates	**1440**	Universal Primer, solvent-free	7
primer for levelled and differently absorbent substrates	**3046**	SOLIMIN Special Primer, solvent-free	11
wall glazing techique	**3110**	Glaze Binder	12
for coloring	**13xx**	Color Pigment	7
masonry			
natural rexin paint	**3011, 3011 1-4**	PRIMASOL Wall Paint, solvent-free, semi mat	11
primer for levelled and differently absorbent substrates	**3046**	SOLIMIN Special Primer, solvent-free	11
mineral silicate paint	**3051, 3051 1-4**	SOLIMIN Mineral Paint, solvent-free	11
primer for levelled and differently absorbent substrates	**3046**	SOLIMIN Special Primer, solvent-free	11
cleaning and maintenance			
oiled and waxed floors			
regular cleaning	**4010, 4020**	NACASA Universal Cleaner, Household Cleaner	12
basic cleaning	**2090**	NAPONA Basic Cleaner	10
intensive oil cleaning	**2057**	Intensive Oil Cleaner	8
regular maintenance	**2085, 2086**	NAPLANA, NAPLANA+ Care Emulsion	9-10
intensive maintenance	**2067, 20671**	Maintenance Oil, colorless / white	9
cash damage or stains	**2081**	Maintenance Set	9
oiled and waxed furniture			
regular cleaning	**4020**	Household Cleaner Spray	12
basic cleaning	**2090**	NAPONA Basic Cleaner	10
regurlar maintenance	**4030**	Wax Care Spray	12
intensive maintenance	**2076, 20761**	Maintenance Oil, colorless / white	9
cash damage or stains	**2081**	Maintenance Set	9
household cleaning			
for all surfaces	**4010, 4020**	NACASA Universal Cleaner / Household Cleaner	12
for tableware	**4053**	NALINDO Washing Up Liquid	13
for windows, glass and plastic surfaces	**4058**	Glass Cleaner	13
for sanitary areas and tiles	**4060**	NATOLE Sanitary Cleaner	13
detergent for delicates and wool	**4056**	NASEDA Wool Detergent	13

Outdoor area

	item no.	product	page
wooden facades, roof substructures, building components, fences, playground equipment			
layer-forming oils	**2043, 20431**	Weather Protection Oil, colorless and colored	8
varnishes	**52011**	Wood Varnish Aqua, colored	14
enamel paints	**5142, 5141**	VERNILUX Aqua Enamel Paint	14
primer	**1211**	Primer Aqua	7
wooden windows and exterior doors			
varnishes	**52011**	Wood Varnish Aqua, colored	14
enamel paints	**5142, 5141**	VERNILUX Aqua Enamel Paint	14
primer	**1211**	Primer Aqua	7
wooden garden furniture			
layer-forming oils	**3752**	Teak Oil for all woods, semi gloss	12
varnishes	**52011**	Wood Varnish Aqua, colored	14
enamel paints	**5142, 5141**	VERNILUX Aqua Enamel Paint	14
primer	**1211**	Primer Aqua	7
wooden terraces and decking			
layer-forming oils	**3753, 37531**	Decking Oil, semi gloss, colorless and colored	12
facades made of plaster, masonry, concrete			
mineral silicate paint	**1405, 1405 1-4**	EUROMIN Facade Paint, solvent-free	7
primer for sanding and highly absorbent substrates	**1440**	Universal Primer, solvent-free	7
cleaning agents			
Intensive cleaning of greyed wood	**2089**	Wood Grey Remover	10
for all surfaces	**4010, 4020**	NACASA Universal Cleaner / Household Cleaner	12
for windows, glass and plastic surfaces	**4058**	Glass Cleaner	13

0500 Thinner

The product is suitable for thinning solvent-based paints, glazes, oils and waxes, as well as for cleaning painting tools. The thinner is also ideal for dissolving oils and resins, removing stains, degreasing and cleaning dirty substrates, removing tannic acid and other problematic ingredients from tropical and tannic acid-containing hardwoods and for de-resinating softwoods.

0600 Brush Cleaner - water based

The brush cleaner is a natural, solvent-free and biodegradable cleaning agent for cleaning brushes, paint rollers, paint rollers, painting tools, varnishing tools, etc. Suitable for removing all solvent-free and water-thinnable natural resin paints, varnishes, glazes, oils and waxes from brushes and tools.

1211 Primer Aqua - solvent-free

Primer Aqua is produced with a binder based on sunflower oil and castor oil. The unevenness levelling, saturating, vapour diffusible and permanently elastic primer provides optimum adhesion for subsequent coats of BIOFA oil and enamel paints on wooden surfaces and wood-based materials.



1301- 1317 Color Pigments - additional product

The Colour Pigments are suitable for colouring and tinting BIOFA PRIMASOL Wall Paint, SOLIMIN Mineral Paint, SOLIMIN Quartz Brush-on Plaster and Glaze Binder. With the exception of Color Pigment 1314 (purple), the pigments are alkali-resistant. Purple must not be used in lime or silicate paints or applied to alkaline-reacting substrates such as new concrete, lime and cement-based plasters, lime and silicate paints.

1405, 1405 1-4 EUROMIN Facade Paint white/colored solvent-free - final coating

EUROMIN is a ready-to-use, solvent-free, UV and weather-resistant silicate paint. It is highly diffusible, light-fast, UV-stable, mould and algae-inhibiting and particularly weather-resistant. It is suitable for uncoated lime and clay plasters, concrete, sand-lime brick and similar mineral substrates as well as old, firmly adhering lime and silicate paint coats. EUROMIN can be tinted in the colours of the BIOFA SILIC color chart.

Complies with standards: DIN 18363/2.4.1. ready-to-use silicate paint made of potassium water glass.



1440 Universal Primer, finxative for wall paints - solvent-free

Universal Primer 1440 is made from natural raw materials and is based on potassium silicate. It saturates, consolidates and equalises highly absorbent and sanding substrates. The product is ideal as a primer for SOLIMIN Mineral Paint 3051, 3051 1-3051 4, 1405 and 1405 1-1405 4 and as a thinner for SOLIMIN Special Primer 3046.



2033 Hard Wax Oil mat - primer and final coat

1 L
16 m²

Hard Wax Oil revitalises the natural structure of the respective substrates and produces a thin film-forming, open-pored, hard-wearing, silky gloss, dirt and water-repellent surface. It revitalises and deepens the natural structure and tone of the treated wood. Hard Wax Oil is ideal as a final treatment for BIOFA Color Oil 2110. (Not for furniture interior surfaces).

Complies with standards: DIBt standard Z-157.10-104 Building authority approval, DIN 53160 Sweat and saliva resistance.

2043, 20431 Weather Protection Oil colorless/colored - primer and final coat

1 L
16 m²

Weather Protection Oil is a very effective wood protection for wooden facades, wooden components, wooden fences or wooden buildings. The oil revives and preserves the natural structure of the wood, protects against moisture and delays the typical greying. It is suitable for sanded, planed and rough sawn wood. Weather protection oil can be tinted in the colours of the BIOFA ELUC color chart for transparent, oily products.

2044 Universal Hard Oil semi mat - primer and final coat

1 L
16 m²

Universal Hard Oil revitalises the natural structure of the respective wood and, thanks to its thin surface film, produces an open-pored, silky matt, hard-wearing, dirt and water-repellent surface that is largely non-yellowing. It is also very suitable as a top coat for Color Oil 2110. BIOFA Universal Hard Oil is a perfect product for customers who want to switch from lacquered surfaces to oiled surfaces.

Complies with standards: DIBt standard Z-157.10-104 Building authority approval, DIN 53160 Sweat and saliva resistance.

2049 Furniture Oil solvent-free - primer and final coat

1 L
50 m²

The Furniture Oil is ideal for absorbent wooden furniture surfaces (not for furniture interior surfaces) and penetrates well into the wood. It revitalises and deepens the natural structure and tone of the treated wood. Furthermore, the natural-based furniture oil creates diffusion-open, hard-wearing, antistatic, dirt and water-repellent surfaces.

Complies with standards: QNG-Ready for KfW funding.

2052 Worktop Oil solvent-free - primer and final coat

1 L
40 m²

The Worktop Oil is suitable for priming and finishing raw wood as well as for maintaining oiled wooden worktops and furniture surfaces (not for furniture interiors). It revitalises and deepens the natural structure and tone of the treated wood. Surfaces treated with worktop oil are breathable, hard-wearing, antistatic and dirt and water repellent.

Complies with standards: QNG-Ready for KfW funding, Food safety, skin compatibility, toy standard EN 71.3.

2055 Hard Wax Oil semi gloss - primer and final coat

1 L
16 m²

Hard Wax Oil revitalises the natural structure of the respective substrates and produces a thin film-forming, open-pored, hard-wearing, silky gloss, dirt and water-repellent surface. It revitalises and deepens the natural structure and tone of the treated wood. Hard Wax Oil 2055 is ideal as a final treatment for BIOFA Color Oil 2110.

Complies with standards: DIBt standard Z-157.10-104 Building authority approval, DIN 53160 Sweat and saliva resistance, QNG-Ready for KfW funding.

2057 Intensive Oil Cleaner

The highly effective cleaner removes heavy dirt as well as old protective and maintenance films on oiled or oiled-waxed wood, cork and linoleum floors that have been treated with BIOFA Universal Hard Oil 2044, Hard Wax Oil 2033, 2055, Furniture Oil 2049, Worktop Oil 2052 or Parquet Oil Special 2059. In principle, the intensive oil cleaner can also be used for other oxidative drying oil systems after prior testing.

2058 Color Paste White - Additional product for BIOFA oils

Color Paste White is a pigment concentrate that can be used to slightly lighten BIOFA oils. By treating the wood surface with a tinted BIOFA oil, light-colored hardwoods and softwoods retain their light natural character. The natural darkening of the wood is greatly reduced. The white color paste can be stirred (up to 10%) into Universal Hard Oil 2044, Furniture Oil 2049, Worktop Oil 2052, Hard Wax Oil 2055, 2033, Parquet Oil Special 2059, Universal Hard Primer 3754 and Universal Hard Primer 3755.

2059 Parquet Oil Special solvent-free - primer and final coat

Parquet oil special refines wood permanently and, after 1 to a maximum of 2 applications, produces a dirt and water-repellent, resistant surface on parquet floors, cork floors, wooden floors ... indoors. It revitalises the natural wood character and gives the wood surface a velvety sheen.

Complies with standards: DIBt standard Z-157.10-104 Building authority approval, NaturePlus 0703-1 708-031-1 and QNG-Ready for KfW subsidisation

1 L
70 m²

The only natureplus-certified floor oil on the market !

2060 Hard Wax semi gloss - final coat

The natural hard wax made from beeswax and carnauba wax is colourless, easy to apply, diffusible, non-slip, antistatic and non-scorching. It forms a silky glossy surface and has a pleasant, mild odour. The hard wax can also be used as a top coat for all BIOFA oils.

Complies with standards: EN 71.3 Children's toy standard

1 L
60 m²

2063 Wax Balm solvent-free - maintenance product and final coat

Wax Finish is an ideal care product for already oiled or oiled-waxed wood and cork surfaces indoors. surfaces in interior areas. This high-quality blend of natural oils, resins and carnauba wax is open-pored, antistatic and moisturising. It is colourless and creates silky-glossy, water-resistant, diffusible, tread-resistant and antistatic surfaces. It can also be used as a top coat for Parquet Oil Special 2059 and Universal Hard Primer 3755.

1 L
80 m²

2076, 20761 Maintenance Oil colorless/white - semi gloss

The solvent-based and semi gloss maintenance oil 2076 (colorless) or 20761 (white) is used in particular as a maintenance product for oiled floor surfaces that appear dull, matt and lean after cleaning. Timely and regular application of BIOFA Maintenance Oil extends the life of treated wood surfaces.

1 L
60 m²

2081 Maintenance Kit - for wooden surfaces which are coated with BIOFA Oils and waxes

Careful cleaning, care and maintenance, e.g. by using the care set oil, are important measures to maintain the quality and beauty of oiled or oiled-waxed cork and wood surfaces in the long term.
The set contains: 150 ml care set oil solvent-free Art. No. 2082, sandpaper P 280, sanding pad brown (coarse), sanding pad white (fine), bamboo cloth, as well as care and repair instructions.

2085 NAPLANA Care Emulsion - solvent-free

This ecological care emulsion is a concentrate and is used for both basic care and routine care. It protects and cares for oiled, glazed, lacquered or waxed floors, smooth leather and other surfaces against dirt and mechanical abrasion. After a short drying time, the care emulsion produces a silky glossy surface without polishing. The treated surfaces are refreshed, diffusible and dirt-repellent.

2086 NAPLANA Plus Care Emulsion, anti-slip protection for floors - solvent-free

This ecological maintenance product is a concentrate and is used for both basic care and routine care. It has an anti-slip effect and protects and cares for oiled, glazed, lacquered or waxed floors, smooth leather and other surfaces against dirt and mechanical abrasion. After a short drying time, the care emulsion produces a silky glossy surface without polishing. The treated surfaces are refreshed, diffusible and dirt-repellent.

2087, 20871 Color Wax colorless/colored - solvent-free

1 L
17 m²

Wood surfaces treated with Color Wax are non-yellowing, silky glossy, diffusible and dirt-repellent. Color Wax can be tinted in the colors of the BIOFA FILUC color chart. When using colored Color Wax, we recommend a final coat of colorless Color Wax to increase abrasion resistance and wipe resistance.
A higher gloss level can be achieved by polishing with a lint-free cloth or a white pad.
Complies with standards: Toy standard EN 71.3 + 9.

2089 Wood Grey Remover

BIOFA Wood Grey Remover can be used to clean, refresh and brighten all greyed, treated and untreated wooden surfaces made of hardwood or softwood. The cleaning agent restores the original colour and therefore the natural, beautiful character of weathered and greyed wooden surfaces. Thanks to its gel-like consistency, the de-greyer also adheres well to sloping or vertical surfaces and can therefore also work perfectly there.

2090 NAPONA Basic Cleaner

This powerful base cleaner is solvent-free, consists of natural raw materials and is highly biodegradable. It removes heavy dirt, oil and wax from wood and cork parquet, linoleum floors, tiles and natural stone floors. After cleaning and neutralisation, the floor should be re-treated with oil or wax.

2091 Floor Soap natural - basic treatment, final treatment and maintenance

Floor Soap natural is a solvent-free, highly concentrated, natural soap combination and is ideal for cleaning and maintaining soaped, leached and oiled softwood floors.
Basic treatment: diluted 1:7 with water
Maintenance: diluted 1:40 with water

2092 Floor Soap white - basic treatment, final treatment and maintenance

Floor Soap white is a solvent-free, highly concentrated, natural soap combination and is ideal for cleaning and maintaining soaped, leached and oiled softwood floors. The soap is particularly suitable for light-coloured woods, as the white pigmentation leaves a beautiful light patina on the surface and delays the natural darkening of the wood.
Basic treatment: Diluted 1:7 with water **Maintenance:** Diluted 1:40 with water

2093 Hard Wood Lye - basic treatment

If hardwoods are treated with hardwood lye, yellowing of the wood can be largely prevented and the actual appearance of the wood surface can be preserved. It is recommended to treat the surface with Floor Soap natural 2091 or Hard Wax 2060.
After-treatment with Floor Soap white 2092 gives the surface a white-rubbed character.

2094 Soft Wood Lye - basic treatment

If softwoods are treated with softwood lye, yellowing of the wood can be largely prevented and the actual appearance of the wood surface can be preserved. It is recommended to treat the surface with Floor soap natural 2091 or Hard Wax 2060.
After-treatment with Floor Soap white 2092 gives the surface a white-rubbed character.

2100, 21001 Stone Oil colorless/colored - final coat



After drying, Stone Oil produces a silky gloss, hard-wearing, dirt and water-repellent, diffusible, film-forming and easy-care surface. Depending on the substrate, it is suitable as a colorless or colored primer and final coat for absorbent mineral substrates such as screed floors, cotto tiles, terrazzo, etc. Color mixtures are available according to RAL or BIOFA ELUC color chart.

Complies with standards: DIN 53160 Sweat and saliva resistance.

2110 Color Oil solvent-free - colored primer



The oil with color pigments is suitable for wood, cork, FU boards, MDF and OSB boards. It penetrates deep into the substrate, revives and deepens the natural structure of the treated substrates and produces a colored surface. Color Oil can be tinted in the colors of the BIOFA ELUC color chart. BIOFA Universal Hard Oil 2044 or Hard Wax Oil 2033, 2055 is recommended as a top coat.

Complies with standards: DIN 53160 Sweat and saliva resistance.

3011, 3011 1-4 PRIMASOL Wall Paint white/colored semi mat - final coat



PRIMASOL is suitable for walls and ceilings, for stable substrates such as plaster, concrete, aerated concrete, plasterboard, cellulose fibreboard, woodchip wallpaper, for renovating old emulsion paints that are stable and clean, and as a primer for glaze painting techniques. The paint is highly opaque, quick-drying and diffusible, breathable and resistant to washing and scrubbing. PRIMASOL can be tinted according to the BIOFA MURIC color chart.

Complies with standards: DIN 13 300 cl. 2 scrub resistance, hiding power cl. 1, flammability class 2

3046 SOLIMIN Special Primer white



SOLIMIN Special Primer 3046 is made from natural raw materials on a silicate basis, is levelling, saturating and diffusible. The product is used as a primer for levelled drywall boards or heavily repaired plaster and mixed substrates on walls and ceilings. Priming with SOLIMIN Special Primer is required if joints and filled areas may show through visibly.

3051, 3051 1-4 SOLIMIN Mineral Paint white/colored - final coat



SOLIMIN is a ready-to-use, diffusion-open, algae and mould-inhibiting silicate paint for walls and ceilings. It can be used on all lime-based, cementitious and gypsum-based plasters, clay plasters, concrete, sand-lime brick, exposed brickwork, woodchip wallpaper, glass fibre fabrics and on old mineral and emulsion paints. SOLIMIN can be tinted with BIOFA Color Pigments 1301-1317 (except 1314) or according to the BIOFA SILIC color chart.

Complies with standards: DIN 18 363 / C 2.4.1 ready-to-use mineral paint, wet abrasion resistance class 2, hiding power class 2, Nature Plus 0602 1001 031 1, QNG-Ready for KfW funding.

3055 SOLIMIN Quartz Brush-on Plaster white - final coat



The ready-to-use quartz brush-on plaster is suitable for lime, cement, clay and gypsum-based plasters, concrete, sand-lime brick, exposed brickwork, old mineral paint coats and emulsion wall paints as well as woodchip wallpaper, plasterboard and gypsum fibreboard. It is open to diffusion, inhibits algae and mould and produces a fine-grained, non-slip surface. It can be used as a base for SOLIMIN Mineral Paint and for glaze painting techniques.

Complies with standards: DIN 18 363/ Part C 2.4.1 ready-to-use silicate render, Nature Plus 0602 1001 031 2, QNG-Ready for KfW funding.

3110 Glaze Binder - final coat

Glaze Binder can be tinted with colored PRIMASOL 30111-30114. Alternatively, the Color Pigments 1301-1317 can also be used for tinting. The glaze binder is quick-drying, relatively smudge-resistant and suitable for plastered and wallpapered walls. Special effects can be achieved with special effects can be achieved using the layering technique, in which several layers of colour are applied on top of each other.

3752 Teak Oil for all woods semi gloss - final coat and maintenance

Teak Oil is ideally suited as a basic treatment and for the care of all untreated or oiled wooden furniture made of bamboo, teak, tropical woods, softwoods and hardwoods. It is a colorless oil, penetrates very well and forms an open-pored, semi gloss and easy-care surface. This optimally protects the wood from moisture and other weather influences.

1 L
13 m²

3753, 37531 Decking Oil colorless/colored - final coat

Decking Oil is a high-quality, impregnating maintenance oil for wooden terraces, walkways or decks made of oak, larch, Douglas fir, robinia, teak, bangkirai and thermowood. It is quick and easy to apply and penetrates deep into the wood to protect it from moisture and weathering. Decking Oil can be tinted in the colors of the BIOFA ELUC color chart for transparent, oily products.

1 L
20 m²

3754 Universal Wood Primer - oily primer

The primer saturates, consolidates and equalises strong and unevenly absorbent substrates. It revitalises and deepens the natural structure and colour of the substrate. Universal Hard Primer is suitable as a primer for highly absorbent or unevenly absorbent mineral floors that are treated with Stone Oil 2100, 21001 as well as for absorbent woods such as walnut, beech or softwood before they are treated with BIOFA Universal Hard Oil 2044, Hard Wax Oil 2033, 2055, Wood Finish 2063 or Hard Wax 2060.

Complies with standards: DIBt standard Z-157.10-104 Building authority approval.

1 L
20 m²

4010 NACASA Universal Cleaner - pH-neutral

NACASA Universal Cleaner is a high-quality and environmentally friendly cleaning concentrate made from natural raw materials without chemical preservatives and free from chlorine, ammonia and phosphate. It is therefore particularly kind to the skin and biodegradable. It is suitable for gentle cleaning of oiled, waxed, varnished and lacquered surfaces such as floors, window frames, doors, tiles, tiles, wood, plastics, etc.

4020 Household Cleaner Spray - pH-neutral

This universal cleaner is a ready-to-use cleaner made from natural raw materials. It is a high-quality universal cleaner without chemical preservatives and free from chlorine, ammonia and phosphate, making it particularly skin-friendly and biodegradable. The spray is suitable for gentle cleaning of oiled, waxed, varnished and lacquered surfaces such as floors, window frames, doors, tiles, tiles, wood, plastics, etc.

Complies with standards: Surface compatibility test.

4030 Wax Care Spray

This ecological care emulsion is a ready-to-use maintenance product. It protects and cares oiled, lacquered, varnished or waxed floors, smooth leather and other surfaces against dirt and mechanical abrasion. After a short drying time, the care emulsion produces a silky-glossy surface without polishing. The treated surfaces are refreshed, diffusible and dirt-repellent.

Complies with standards: Surface compatibility test.

BIOFA Naturprodukte W. Hahn GmbH ◆ Dobelstraße 22 ◆ D-73087 Bad Boll ◆ T: +49 7164-9405 0 ◆ F: +49 7164-9405 96 ◆ www.biofa-de.com ◆ info@biofa-de.com

4053 NALINDO Washing Up Liquid - particularly skin-friendly

This hand dishwashing liquid is alkali-free, phosphate-free and contains no chemical preservatives. Thanks to the addition of lecithin, the washing-up liquid cares for the hands when rinsing and prevents the skin from drying out. The washing raw materials contained in NALINDO (surfactants from vegetable fats) have very good dirt and grease dissolving properties and give dishes, glasses and pots a beautiful shine.

4056 NASEDA Wool Dtergent - for wool, silk and delicate fabrics

This ecological hand wash is made from natural raw materials, without chemical preservatives and free from enzymes, optical brighteners, softeners and phosphates. The washing raw materials used (surfactants from vegetable fats) have very good dirt and grease dissolving properties. Nevertheless, the environmentally friendly wool detergent concentrate is mild and gentle on the laundry. It cares for woollens and delicates during washing!

4058 Glass Cleaner

This glass cleaner consists of 100% high-quality natural raw materials, is produced without preservatives and is very environmentally friendly. It easily removes stubborn dirt and ensures cleanliness and a streak-free, beautiful shine on the respective surfaces. The ecological cleaning agent is suitable for windows, mirrors, glass tables, glass cabinets, car windscreens, etc. as well as for cleaning demanding plastic surfaces, window frames, doors or tiles.

4060 NATOLE Sanitary Cleaner

This highly effective sanitary cleaner is ideal for gentle and environmentally friendly cleaning of bathrooms, toilets and kitchens. It effectively removes heavy soiling, limescale and urine scale from toilet bowls, urinals, washbasins, bathtubs, shower trays, tiles (tiles), fittings, etc. and provides natural, fresh-smelling cleanliness with a radiant shine.

4085 Cleaning and Maintenance Kit

BIOFA Cleaning and Maintenance Kit is suitable for the regular cleaning and care of all oiled and waxed wooden surfaces indoors. It contains 500 ml NACASA Universal Cleaner 4010, 500 ml NAPLANA Care Emulsion 2085, cleaning and care instructions and a bamboo cloth, all the utensils you need to enjoy your natural wood surface for a long time.

5005 Natural Shellac Enhancer - primer and final coat

This wood finish is made from natural raw materials based on shellac. It is colorless, solvent-free, water-dilutable, quick-drying and saturates the wood. The solvent-free Natural Shellac Enhancer is ideally suited as a top coat for cabinet interiors and drawers, as the product is completely odourless and dries very quickly.

Complies with standards: Toy standard EN 71.3

1 L
20 m²

5135, 5134 VERNILUX Aqua Enamel Paint interior, white/colored semi mat - final coat

VERNILUX Aqua 5135, 5134 is a water-thinnable, dirt and water-repellent paint. It has very good adhesion and high hiding power. The lacquer is suitable for all wooden surfaces (not for furniture interior surfaces). After pre-treatment with a commercially available, suitable rust inhibitor, it is also suitable for metal substrates, e.g. heating elements. VERNILUX Aqua 5134 can be tinted in all RAL colors.

Complies with standards: EN 71.3 Toy standard, DIN 53160 Welding and saliva resistance.

1 L
14 m²

5136 VERNILUX Aqua Enamel Paint interior, white/colored semi glossy - final coat

VERNILUX Aqua 5136 is a water-thinnable, dirt and water-repellent paint. It has very good adhesion and high hiding power. The lacquer is suitable for all wooden surfaces (not for furniture interior surfaces). After pre-treatment with a commercially available, suitable rust inhibitor, it is also suitable for metal substrates, e.g. heating elements.

Complies with standards: EN 71.3 Toy standard, DIN 53160 Welding and saliva resistance.

1 L
14 m²

5142, 5141 VERNILUX Aqua Enamel Paint exterior, white/colored semi glossy - final coat

VERNILUX Aqua 5142, 5141 is weatherproof, dirt and water repellent and resistant. It has good coverage and adhesion. The wood surface remains permanently elastic, breathable and antistatic. VERNILUX Aqua is suitable for protecting wooden components such as wooden facades, gates, windows, doors, railings, fences, garden furniture and play equipment. With appropriate pre-treatment, it can also be used on metal substrates. VERNILUX Aqua 5141 can be tinted in all RAL colors.

Complies with standards: EN 71.3 Toy standard, DIN 53160 Welding and saliva resistance.

1 L
14 m²

5201, 52011 Wood Varnish Aqua colorless/colored semi glossy - primer and final coat

Wood Varnish Aqua is suitable for all hardwoods and softwoods. This wood stain produces an open-pored, hard-wearing, highly elastic, dirt and water-repellent surface. It is transparent and revitalises and deepens the natural structure of the treated wood. Wood Varnish Aqua can be tinted in the colours of the BIOFA FILUC color fan for transparent, water-based products.

Complies with standards: EN 71.3 Toy standard, DIN 53160 Welding and saliva resistance.

1 L
14 m²

5295 Varnish Renewal Aqua colorless - maintenance and renovation product

Coated wooden elements in outdoor areas are exposed to a great deal of stress due to weathering and UV radiation. Varnish Refresher Aqua is a solvent-free, water-based care emulsion for exterior and interior glaze coatings. When used regularly, it extends the renovation intervals and therefore the service life of glaze coatings in exterior areas by forming a thin binder layer on the glaze surface, which refreshes and protects it and gives it a new lustre.

1 L
65-100 m²

2108 Color Stabilizer - additional product

Color Stabilizer is a transparent stabiliser on a natural basis. It is suitable for all BIOFA oil systems on light-colored substrates. It allows light-colored surfaces to retain their light character to a large extent by reducing the natural yellowing of the oils and resins.

2146 Retarding agent - additional product for 8045 and 8245

this drying retarder is an optional additive for Hard Oil Aqua silk matt item no. 8045 and Hard Oil Aqua matt item no. 8245 as well as for all water-based BIOFA oils and lacquers. It slows down the relatively rapid setting and drying of the products and thus extends the open time. This enables significantly longer wet-on-wet work, especially on large surfaces.

8005, 80051-800515 Toy Paint colorless/colored - transparent primer

No solvents and no harmful substances for our children! Toys that also shine in many bright colours make children's eyes light up. By mixing the 10 colours on offer, you can create a bright and colourful variety. The toy paint is odourless, particularly well tolerated - even by allergy sufferers, very easy to use and dries extremely quickly. To avoid colour abrasion, we recommend BIOFA Hard Oil Aqua matt 8245 as the final coat.

Complies with standards: Toy standard EN 71.3.

8045 Hard Oil Aqua semi gloss - primer and final coat



Hard Oil Aqua 8045 is a water-dilutable coating for the efficient, time-saving surface treatment of interior wooden surfaces. It revitalises the natural structure of the treated substrates and produces a hard-wearing and water-repellent surface that is largely non-yellowing.

Complies with standards: EN 71.3 toy standard, DIN 53160 sweat and saliva resistance.

8081 Bianco Maintenance Set - for surfaces oiled with Bianco Oil 8683

Careful cleaning, care and maintenance are important measures for preserving the quality and beauty of oiled wooden surfaces in the long term. The care and repair set contains: 150 ml BIOFA Bianco Oil 8683 solvent-free Art. No. 8683, sandpaper P 240, sanding pad gray (coarse), sanding pad white (fine), bamboo cloth, as well as care and repair instructions.

8101, 81011 Wood Varnish Aqua Industry colorless/colored - primer and final coat



Wood Varnish Aqua Industry is a water-thinnable, very fast-drying wood stain. It forms a weather-resistant, silky-glossy surface that is highly elastic and water-repellent.
Aqua wood stain can be tinted ex works in many colors according to the BIOFA FILUC color fan.

Complies with standards: EN 71.3 Toy standard.

8245 Hard Oil Aqua mat - primer and final coat



Hard Oil Aqua 8245 is a water-dilutable coating for the efficient, time-saving surface treatment of interior wooden surfaces. It revitalises the natural structure of the treated substrates and produces a hard-wearing and water-repellent surface that is largely non-yellowing.

Complies with standards: EN 71.3 toy standard, DIN 53160 sweat and saliva resistance.

8624, 86241 Profi Top Oil colorless/colored semi gloss - primer and final coat

BIOFA Profi Top Oil is a high-quality product made from natural raw materials on the basis of an oil-resin compound. It refines the wood permanently and produces a resistant, diffusion-open and antistatic surface. The natural character of the wood is emphasised and the surface is given a velvety sheen. Profi Top Oil can be tinted ex works in many colours according to the BIOFA ELUC colour chart.

Complies with standards: Parquet standard DIN EN 14342 (DIBt).

1 L
33-50 m²

8683 Bianco Oil, raw wood effect - primer and final coat

Bianco Oil is a high-quality coating for the rational, time-saving surface treatment of interior wooden surfaces. The natural color of the wood remains largely unchanged after treatment - raw wood effect, there is hardly any staining. The result is a matt, open-pored, hard-wearing, dirt and water-repellent surface that is largely non-yellowing.

Complies with standards: DIBt standard Z-157.10-104 building authority approval, DIN EN 14342 parquet standard.

1 L
15-25 m²

8689 Bianco Oil Aqua, raw wood effect - primer and final coat

Bianco Oil Aqua is a water-dilutable coating for the efficient, time-saving surface treatment of interior wood surfaces. The natural character of the treated wood surface is retained - raw wood effect, resulting in a colorless, matt, hard-wearing and water-repellent surface that is UV-protected and non-yellowing.

Complies with standards: EN 71.3 toy standard, DIN 53160 sweat and saliva resistance.

1 L
13-17 m²

BIOFA Naturprodukte W. Hahn GmbH
Dobelstraße 22 ◆ 73087 Bad Boll
T: +49 (0) 7164 / 9405 0
F: +49 (0) 7164 / 9405 96
www.biofa-de.com ◆ info@biofa-de.com